

PRODUCT SPECIFICATION SHEET

Item Name : New Wave Prima

Specifications :

- Contents : Top - 100% PVC with exclusive PointeShield™
Back – 100% Polyester
- Width : 54"
- Nominal thickness : 0.044/48 inches
- Nominal weight : 32oz/linear yard
- Repeat : N/A
- Roll Length : App. 30/35yds

General Characteristics :

- Superior wear resistance : Exceeds 100,000 rubs (ASTM D4157 Wyzenbeek)
- Anti-bacterial/Anti-microbial (AATCC-147)
- Colorfastness to light (AATCC-16/passes)
- Colorfastness to bleach (AATCC-3): passes 1:10&1:5 dilution test
- Resistance to heat aging (EDS T7604)
- Resistance to various stains (MS 300-32 4.21)
 - Oil, Grease, Nicotine, Tar, Mud, etc.
- -20 degree F cold crack resistant (MIL-C-20696C)
- Mildew resistant backing

Flammability :

- CA Bulletin 117 – Class A
- UFAC/NFPA Class 1
- BIFMA – Class A
- FMVSS-302
- IMO A652 (16) 8.2 & 8.3
- ASTM E-84 (Adhered) Class A

Care & Cleaning : Exclusive PointeShield™ protection for easy care, stain-free surface.

- 1) Most stains and ballpoint pen marks* can be easily wiped out with a clean dry towel.** No need to use complicated cleaning procedures.

- 2) Spot clean the spilled area with mild soap and water.
- 3) Rubbing alcohol (isopropyl alcohol)*** can be used to clean any remaining stain. Rinse the cleaned area with clean water and dry with air or lint-free cloth.

Disinfectability : This item is formulated to achieve a superior level of disinfectability with a 10:1 bleach solution.

Warranty : Please refer to our Terms of Sales for warranty information.

*PointeShield does not protect the product against intentional stains such as permanent marker.

**Use non-abrasive soft cloth/napkin to avoid scratching of the surface.

***Caution: Exercise care as alcohols are flammable. Use only small amount and keep clear of any source of ignition. Wear protective gloves during cleaning activities.